

FLR2X-B

低压汽车电线

-40℃~+125℃/3000h

Low-tension cables for automobiles



产品特点:

薄壁，耐热

导体:

导体由软圆铜线绞合而成。

绝缘材料:

辐照交联聚烯烃

执行标准:

ISO 6722:2011 Class C

包装方式: 成圈，成箱，成盘，成桶。

FEATURE:

Thin-walled , Heat-resistant

CONDUCTOR:

The conductor was stranded with soft-annealed copper

INSULATION:

XLPO

STANDARD:

ISO 6722:2011 Class C

FORM OF DELIVERY: On reels, boxes, drums, barrels.

导体/Conductor				电线/Cable	
标称截面 Nominal Cross-section mm ²	结构 Number of single wires/ Max. dia. of strand Pcs/mm	最大电阻 Resistance (20℃) mΩ/m	最大外径 Outside diameter mm	最小厚度 Insulation thickness Min. mm	最大外径 Outside Diameter Max. mm
0.35	12/0.21	54.4	0.90	0.20	1.40
0.50	16/0.21	37.1	1.10	0.22	1.60
0.75	24/0.21	24.7	1.30	0.24	1.90
1.0	32/0.21	18.5	1.50	0.24	2.10
1.5	30/0.26	12.7	1.80	0.24	2.40
2.0	28/0.31	9.42	2.00	0.28	2.80
2.5	50/0.26	7.60	2.20	0.28	3.00
3	44/0.31	6.15	2.40	0.32	3.40
4	56/0.31	4.71	2.80	0.32	3.70
5	70/0.31	3.94	3.10	0.32	4.20
6	84/0.31	3.14	3.40	0.32	4.30
10	80/0.41	1.82	4.50	0.48	6.00
16	126/0.41	1.16	6.30	0.52	7.90
25	196/0.41	0.743	7.80	0.52	9.40



北京斯普乐电线电缆有限公司
Beijing S.P.L Wire & Cable Co.,Ltd

Tel: 86-10-61665369
Fax: 86-10-61667272
Web: www.spl-cable.com