



产品特点:

薄壁，耐热

导体:

导体由软圆铜线绞合而成。

绝缘材料:

交联聚烯烃

执行标准:

SAE J1128

包装方式: 成圈，成箱，成盘，成桶。

FEATURE:

Thin-walled , Heat-resistant

CONDUCTOR:

The conductor was stranded with soft-annealed copper

INSULATION:

XLPO

STANDARD:

SAE J1128

FORM OF DELIVERY: On reels, boxes, drums, barrels.

导体/Conductor				电线/Cable	
线规号 AWG	标称截面 Nominal Cross-section mm ²	结 构 Number of single wires/ dia. of strand Pcs/mm	最小截面 Minimum Area mm ²	最小厚度 Insulation thickness Min. mm	最大外径 Outside Diameter Max. mm
24	0.22	7/0.20	0.205	0.28	1.50
22	0.35	7/0.254	0.324	0.28	1.70
20	0.5	7/0.32	0.508	0.28	1.90
18	0.8	19/0.23	0.760	0.28	2.20
16	1	19/0.28	1.12	0.28	2.40
14	2	19/0.36	1.85	0.28	2.70
12	3	19/0.45	2.91	0.32	3.30
10	5	19/0.57	4.65	0.35	4.00
8	8	19/0.71	7.23	0.39	4.90